



FLUORESCENT TUBE CARRIER

Fluorescent lights are fragile and can break if not handled properly. The fluorescent tube carrier features a rubber padded base designed to provide a soft resting spot, and is equipped with a buckle strap to secure and safely carry the fluorescent lights to their work location.

Ideal for maintenance needs, the fluorescent tube carrier is mounted outside the platform to optimize work space and increase productivity.



Use only on listed models	VERTICAL MAST LIFTS				
Model Serial Number	Platform Capacity (including load on Tube Carrier)	Height	Rated load on Tube Carrier	Horizontal Load Rating (Manual Force)	Wind Rating
SJ12 A600 000 001+, 140 000 00+	500 lb (227 kg) 1 person	12 ft (3.66 m)	50 lb (23 kg)	45 lbf (200 N)	28 mph (12.5 m/s)
SJ16* A600 000 001+, 140 000 00+	500 lb (227 kg) 1 person	12 ft (3.66 m)	50 lb (23 kg)	45 lbf (200 N)	28 mph (12.5 m/s)
	500 lb (227 kg) 1 person	16 ft (4.88 m)	50 lb (23 kg)	45 lbf (200 N)	0 mph (0 m/s)
SJ20 601000001+	350 lb (159 kg) 1 person	19.5 ft (5.94 m)	50 lb (23 kg)	45 lbf (200 N)	0 mph (0 m/s)
SJ12 E A601000906 - A601999999	500 lb (227 kg) 1 person	12 ft (3.66 m)	50 lb (23 kg)	45 lbf (200 N)	0 mph (0 m/s)
SJ16 E A601000906 - A601999999	500 lb (227 kg) 1 person	16 ft (4.88 m)	50 lb (23 kg)	45 lbf (200 N)	0 mph (0 m/s)
SJ20 E A601000906 - A601999999	350 lb (159 kg) 1 person	19.5 ft (5.94 m)	50 lb (23 kg)	45 lbf (200 N)	0 mph (0 m/s)

Overall tube carrier weight (unloaded) 17 lb (7.7 kg)
* With Wind Rating Option Only

Skyjack Head Office
55 Campbell Rd.
Guelph, ON Canada N1H 1B9
Sales Inquiries: 1-877-755-4387 (1-877-SJLIFTS)
Main Switchboard: 1-800-265-2738
Phone: 519-837-0888
Fax: 519-837-8104
Email: skyjack@skyjack.com

Skyjack Parts & Service
2525 Enterprise Circle
West Chicago, IL 60185 USA
Phone: 630-262-0005
Toll Free: 1-800-275-9522
Fax: 630-262-0006
Email: service@skyjack.com

SKYJACK
simply reliable

www.skyjack.com/accessoryzers